



INLET & DISCHARGE FLANGES TO MATE FLUSH & SQUARE WITH FLAT FACE FLANGE ONLY. USE FULL FACE GASKETS.

V-BELT DRIVEN UNITS: MOTOR TO BE LOCATED ON INLET SIDE OF BLOWER.

AD - MAXIMUM SHEAVE WIDTH (SEE OVERHUNG LOAD LIMIT K-24102)

AE - MINIMUM SHEAVE DIAMETER (SEE OVERHUNG LOAD LIMIT K-24102)

ALL DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED METRIC DIMENSIONAL #92518021

ANSI FLANGE DIMENSIONS						
	FA	FB	FC	FD	FE	FG
10 FLG	10.00	14.25	16.00	12	.88-9	1.19
12 FLG	12.00	17.00	19.00	12	.88-9	1.25

FA - FLANGE OPENING
 FB - FLANGE BOLT CIRCLE
 FC - FLANGE D.D.
 FD - No. TAPPED HOLES
 FE - SIZE OF TAPPED HOLES
 FG - DEPTH OF TAP

DRIVE LOCATION		
	LH	RH
DISCH. LOCATION TOP	CW	CCW
DISCH. LOCATION BOTTOM	CCW	CW

UNIT IS BUILT TO CUSTOMERS SPECIFIED ORIENTATION

MODEL	A	A'	B	C	D	D'	E	E'	F	G	H	J	K	M	N	O	P	R	U	V	KEYWAY	INLET	DISCH	AB	AD	AE	AF	FLANGE SIZE	APPROX WEIGHT
722	19.00	26.00	28.79	41.17	17.00	10.00	7.25	10.75	13.27	.50	1.00	4.50	3.00	16.14	4.56	25.13	29.75	13.5	60.00	76.20	18.0X7.0	14.87	14.87	1.63	4.43	11.80	23.26	10"	1485 LBS
728	"	"	34.54	46.92	"	"	"	"	16.14	"	"	"	"	19.01	"	"	31.88	"	"	"	"	15.94	15.94	"	"	"	"	12"	1805 LBS

CERTIFIED CORRECT FOR	Δ	UPDATE TO HOWDEN, TRI-RAM BRAND	MPM	16849V	MNM	V-BELT DRIVE DATA
CUSTOMER ORDER No.	Δ	REF FLANGE HOLES TO STRADDLE C/L		11895V		BELTS
ROOTS ORDER No.	Δ	REV OF DIM "F"		11471H		DRIVE SHEAVE
DATE	Δ	ORACLE CONVERSION				DRIVEN SHEAVE
REVISIONS		BY	CHANGE NOTICE	CHKD.	APP.	CENTER DISTANCE

TRI-RAMTM

TRI-LOBE BLOWERS MODELS 722 & 728

Connersville, IN USA
 P: 765-827-9200
 F: 765-827-9266

Howden

DR	CHKD	APP	92517021	REV. D
----	------	-----	-----------------	--------